



MovieTech

Time is money, this expression is especially true on a film set

For the same reason many crews select the Felix crane for their productions. From a light dolly to a professional crane with platform, the Felix Crane can be mounted to fit your requirements.



The Felix Crane System

The Felix Crane as..



With the modular Felix Crane System it is possible to set up for remote-head or platform use within minutes. The maximum heights of the standard Felix crane are: with platform for 1 person approx. 3,5 m/12' ; with remote head mount approx. 450 cm/15' .

The basic Felix crane can be extended within a short time to many different lengths. Made of Aluminium alloy the crane weighs in the Felix IV version (ridge: 450 cm / 14'9") around 150 Kg (without counterweight).

Felix Version I (Platform)



Max. Euroadapter height:	9'1"
Lift range:	8'6"
Max. Euroadapter depth:	5"
Weight crane + dolly:	327 lbs
Max. working load:	484 lbs
Max. counterweight:	739 lbs

The Felix Crane is TÜV certified

Felix Version II (Platform)



Max. Euroadapter height:	11'7"
Lift range:	13'8"
Max. Euroadapter depth:	- 2'1"
Weight crane + dolly:	343 lbs
Max. working load:	286 lbs
Max. counterweight:	844 lbs

The Felix Crane is TÜV certified

Felix Version III (Remote)



Max. Euroadapter height:	12'4"
Lift range:	13'8"
Max. Euroadapter depth:	- 1'4"
Weight crane + dolly:	316 lbs
Max. working load:	176 lbs
Max. counterweight:	448 lbs

The Felix Crane is TÜV certified

Felix Version IV (Remote)



Max. Euroadapter height:	15'
Lift range:	19'
Max. Euroadapter depth:	- 4'
Weight crane + dolly:	338 lbs
Max. working load:	132 lbs
Max. counterweight:	563 lbs

The Felix Crane is TÜV certified